

View Online at <https://aerobasegroup.com/nsn/5985-01-105-5364>

**Application Design:**

Transmission line

**Body Material:**

Steel

**Body Style:**

Err-090

**Body Surface Treatment:**

Any acceptable

**Overall Length:**

1.234 inches

**Overall Diameter:**

0.625 inches

**Voltage Standing Wave Ratio:**

1.25 and 1.40

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

5.5 watts average and 200.0 watts peak

**Rf Signal Attenuation In Decibels:**

20.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz and +4.0/+6.0 gigahertz

**Attenuation Accuracy Reference Frequency:**

6.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Connection Type Per Function:**

Female output and male input

**Unpackaged Unit Weight:**

0.500 ounces

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 6.000 gigahertz

**Precious Material And Location:**

Center conductor surfaces gold

**Precious Material:**

Gold

**Specification Data:**

49671-2396070 manufacturers specification control

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000