NSN 5985-01-105-8541

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-105-8541 **Application Design:** Transmission line **Body Material:** Steel **Body Style:** Err-090 **Overall Length:** 1.490 inches **Overall Diameter:** 0.380 inches **Operating Tempurature Range:** -54.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.25 and 1.40 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 200.0 watts peak **Rf Signal Attenuation In Decibels:** 40.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+6.0 gigahertz **Attenuation Accuracy Reference Frequency:** 6.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female output and male input **Unpackaged Unit Weight:** 0.500 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 6.000 gigahertz **Fsc Application Data:**

Antennas, waveguides, and related equipment

NSN 5985-01-105-8541

Fixed Attenuator - Page 2 of 2



	L -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000