NSN 5985-01-106-7639

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-106-7639

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches
Overall Height:
3.000 inches
Overall Width:
3.850 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 7.000 gigahertz and 12.400 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:

0.164 inches

NSN 5985-01-106-7639

Variable Attenuator - Page 2 of 2



50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A223a0