NSN 5985-01-107-0599

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-107-0599

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b single flange all connection facilities

Thread Direction:

Right-hand single flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.255 inches second flange

Flange Inside Height:

0.630 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.531 inches single flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches single flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 single flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

1.875 inches

Thread Size:

0.164 inches single flange all connection facilities

Waveguide Inside Width:

1.255 inches

Waveguide Inside Height:

0.630 inches

Waveguide Outside Height:

1.875 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

NSN 5985-01-107-0599 Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type second flange
Waveguide Center To Center Distance:
6.500 inches
Waveguide Height:
8.500 inches
Flexibility:
Flexible single tubing segment
Material:
Copper alloy single tubing segment
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Double bend type
Thread Series Designator:
Unc single flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0