## NSN 5985-01-107-0979

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-107-0979

Application Design:
Transmission line
Body Style:
Cylindrical w/adjustment knob
Overall Length:
4.560 inches
Bolt Circle Diameter:
5.125 inches
Scale Linearity:
Nonlinear
Scale Division Quantity:
70
Overall Diameter:
5.000 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.000 gigahertz and 1.180 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position circular
Mounting Facility Screw Thread Diameter:

0.164 inches

## NSN 5985-01-107-0979

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lmp	edance	Rating	In	<b>Ohms</b>
--------------------------	-----	--------	--------	----	-------------

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0