NSN 5985-01-108-3636

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-108-3636

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 third bend h-plane

End Application:

5840-01-046-7622, radar group, an/mst-t1

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange

Flange Inside Height:

0.628 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

NSN 5985-01-108-3636 Waveguide Assembly - Page 2 of 2



Waveguide First Leg Length:
2.030 inches
Flange Style:
Cover type second flange
Waveguide Second Leg Length:
3.120 inches
Waveguide Third Leg Length:
4.500 inches
Waveguide Fourth Leg Length:
1.900 inches
Special Features:
First leg is 2.030 in. Lg with e-plane 90 degree bend, 3.120 in. Lg; 4.500 in. Lg leg has h-plane 90 degree bend, 1.900 in. Lg
Flexibility:
Rigid all tubing segment
Material:
Aluminum alloy 6061 single tubing segment and flange
Style Designator:
Three bend type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0