NSN 5985-01-108-9198

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-108-9198

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b single flange all connection facilities

Thread Direction:

Right-hand single flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

75.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.007 inches second flange

Flange Inside Height:

1.507 inches second flange

Flange Outside Diameter:

5.313 inches second flange

Flange Depth:

1.250 inches first flange

Flange Connecting Hole Diameter:

0.257 inches single flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Thready Qty Per Inch (tpi):

20 single flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

3.000 inches

Thread Size:

0.250 inches single flange all connection facilities

Waveguide Inside Width:

2.840 inches

Waveguide Inside Height:

1.340 inches

Waveguide Outside Height:

1.500 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

NSN 5985-01-108-9198

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Length: 2.000 feet Flexibility: Flexible single tubing segment Material: Rubber synthetic single tubing jacket **Precious Material And Location:** Waveguide surfaces silver **Precious Material:** Silver Surface Treatment: Silver single tubing segment all surfaces **Style Designator:** Straight type **Thread Series Designator:** Unc single flange all connection facilities Shelf Life: N/a Unit Of Measure: ---Demilitarization:

No

Fiig: A073a0