## NSN 5985-01-108-9206

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-108-9206

## **Cross Sectional Shape:**

Internal, rectangular external, round

**Thread Class:** 

2a single flange all connection facilities

**Thread Direction:** 

Right-hand single flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

**Tubing Twist Type:** 

Straight twist single tubing segment

**Tubing Twist Angle In Deg:** 

105.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.006 inches second flange

Flange Inside Height:

1.006 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.199 inches single flange all connection facilities

**Voltage Standing Wave Ratio:** 

1.06

Thready Qty Per Inch (tpi):

32 single flange all connection facilities

**Maximum Operating Pressure:** 

30.0 pounds per square inch gage

**Thread Size:** 

0.190 inches single flange all connection facilities

Waveguide Inside Width:

2.006 inches

**Waveguide Inside Height:** 

1.006 inches

**Waveguide Outside Diameter:** 

3.625 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

## **NSN 5985-01-108-9206** Waveguide Assembly - Page 2 of 2



Waveguide Length:
1.250 feet
Flexibility:
Flexible single tubing segment
Material:
Copper alloy single tubing segment
Precious Material And Location:
Waveguide external surfaces silver
Precious Material:
Silver
Surface Treatment:
Paint all tubing segment and flange inside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unf single flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
<del>.</del> -
Demilitarization:
No
Fiig:
A073a0