

View Online at <https://aerobasegroup.com/nsn/5985-01-109-3616>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Interlocked single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

105.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.000 inches all flanges

Flange Inside Height:

1.000 inches all flanges

Flange Outside Diameter:

3.625 inches all flanges

Flange Depth:

0.375 inches all flanges

Flange Connecting Hole Diameter:

0.199 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.06

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

9.000 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Precious Material And Location:

Waveguide surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver single tubing segment all surfaces

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0