## NSN 5985-01-109-8538

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-109-8538

**Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 6.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.135 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 2.130 inches **Overall Height:** 0.380 inches **Overall Width:** 2.130 inches **Unthreaded Mounting Hole Diameter:** 0.160 inches **Voltage Standing Wave Ratio:** 1.80 **Coaxial Connector Series Designation:** Sma **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.6 **Overall Attenuation Range In Decibels:** +0.0/+28.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 1.000 gigahertz and 2.000 gigahertz **Adjustment Device Type And Quantity:** 1 electronic, programmable **Mounting Facility Pattern:** Four position rectangular **Terminal Type And Quantity:** 3 connector, coaxial, female Shelf Life: N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5985-01-109-8538

Variable Attenuator - Page 2 of 2



Fiig:

A223a0