NSN 5985-01-109-9115

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-109-9115 **Application Design:** Transmission line **Body Material: Brass Terminal Surface Treatment:** Any acceptable **Body Surface Treatment:** Any acceptable **Overall Length:** 4.000 inches **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 2.0 watts average and 0.2 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy In Decibels:** -1.00/+1.00 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz **Precious Material And Location:** Connector body silver **Precious Material:** Silver **Fsc Application Data:** Antennas, waveguides, and related equipment

Shelf Life: N/a

NSN 5985-01-109-9115

Fixed Attenuator - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000