

View Online at <https://aerobasegroup.com/nsn/5985-01-109-9117>

Application Design:

Transmission line

Body Material:

Brass

Terminal Material:

Copper alloy

Terminal Surface Treatment:

Any acceptable

Body Surface Treatment:

Any acceptable

Overall Length:

4.000 inches

Voltage Standing Wave Ratio:

1.15 and 1.20 and 1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

N

Power Rating:

2.0 watts average and 0.2 kilowatts peak

Rf Signal Attenuation In Decibels:

10.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Connector body silver

Precious Material:

Silver

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000