NSN 5985-01-110-2534

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-110-2534

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.125 inches
Bolt Circle Diameter:
1.125 inches
Overall Height:
2.531 inches
Overall Width:
1.785 inches
Scale Linearity:
Linear
Coaxial Connector Series Designation:
Bnc
Power Rating:
10.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.4
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 hertz and 500.000 megahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position circular
Mounting Facility Screw Thread Diameter:

0.164 inches

NSN 5985-01-110-2534

Variable Attenuator - Page 2 of 2



	Impedance	Rating	ln	Ohms:
--	-----------	--------	----	-------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0