NSN 5985-01-110-2534

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-110-2534

| Ap | plica | ition | Design: |
|----|-------|-------|---------|

Transmission line

Body Style:

Coaxial type

Overall Length:

3.125 inches

Bolt Circle Diameter:

1.125 inches

Overall Height:

2.531 inches

Overall Width:

1.785 inches

Scale Linearity:

Linear

Coaxial Connector Series Designation:

Bnc

Power Rating:

10.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.4

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

10

Attenuation Per Step In Decibels:

1.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 0.000 hertz and 500.000 megahertz

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position circular

Mounting Facility Screw Thread Diameter:

0.164 inches

NSN 5985-01-110-2534

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0