## NSN 5985-01-110-3388

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-110-3388

| Application Decima  |
|---|
| Application Design:   |
| Transmission line   |
| Body Style:   |
| Coaxial type  |
| Overall Length:   |
| 1.350 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.500 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.470 inches  |
| Overall Height:   |
| 0.790 inches  |
| Overall Width:  |
| 0.750 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.040 inches  |
| Operating Tempurature Range:  |
| -54.0/+100.0 degrees celsius  |
| Voltage Standing Wave Ratio:  |
| 2.00  |
| Power Rating:   |
| 0.5 watts average   |
| Insertion Loss At Minimum Attenuation In Maximum Decibels:                |
| 2.0   |
| Overall Attenuation Range In Decibels:                                    |
| +0.0/+10.0  |
| Attenuation Variation Method:   |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 4 unthreaded hole   |
| Frequency Range:  |
| Between 0.000 hertz and 400.000 megahertz                                 |
| Adjustment Device Type And Quantity:                                      |
| 1 slotted screw   |
| Mounting Facility Pattern:  |
| Four position rectangular   |
| Impedance Rating In Ohms:   |
|   |
| 50.0 input-output   |
| 50.0 input-output  Terminal Type And Quantity:                            |
|   |

N/a

## NSN 5985-01-110-3388

Variable Attenuator - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A223a0