## NSN 5985-01-110-3388

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-110-3388

Application Decima						
Application Design:						
Transmission line						
Body Style:						
Coaxial type						
Overall Length:						
1.350 inches						
Center To Center Distance Between Mounting Facilities Parallel To Length:						
0.500 inches						
Center To Center Distance Between Mounting Facilities Parallel To Width:						
0.470 inches						
Overall Height:						
0.790 inches						
Overall Width:						
0.750 inches						
Unthreaded Mounting Hole Diameter:						
0.040 inches						
Operating Tempurature Range:						
-54.0/+100.0 degrees celsius						
Voltage Standing Wave Ratio:						
2.00						
Power Rating:						
0.5 watts average						
Insertion Loss At Minimum Attenuation In Maximum Decibels:						
2.0						
Overall Attenuation Range In Decibels:						
+0.0/+10.0						
Attenuation Variation Method:						
Continuous						
Mounting Facility Type And Quantity:						
4 unthreaded hole						
Frequency Range:						
Between 0.000 hertz and 400.000 megahertz						
Adjustment Device Type And Quantity:						
1 slotted screw						
Mounting Facility Pattern:						
Four position rectangular						
Impedance Rating In Ohms:						
50.0 input-output						
Terminal Type And Quantity:						
4 pin						

N/a

## NSN 5985-01-110-3388

Variable Attenuator - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A223a0