NSN 5985-01-110-6764

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-110-6764

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.005 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Inside Diameter:

1.422 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

60.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

NSN 5985-01-110-6764 Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type second flange
Waveguide Length:
3.500 feet
Flexibility:
Flexible single tubing segment
Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
External surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver all tubing segment and flange outside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0