## NSN 5985-01-113-3037

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-113-3037 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 0.600 inches **Overall Height:** 0.750 inches **Overall Width:** 1.350 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.600 inches **Operating Tempurature Range:** +0.0/+65.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 **Power Rating:** 0.5 watts average **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 1.5 **Overall Attenuation Range In Decibels:** +0.0/+20.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 1 threaded stud Frequency Range: Between 0.000 hertz and 225.000 megahertz **Adjustment Device Type And Quantity:** 1 slotted screw and 1 shaft **Shaft Type:** Round, slotted Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 4 pin Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5985-01-113-3037

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0