## NSN 5985-01-113-4182

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-113-4182

Application Decima
Application Design:  Transmission line
Body Style:
Coaxial type
Overall Length:
Between 2.700 inches and 2.930 inches
Shaft Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
0.750 inches
Operating Tempurature Range:
-57.0/+70.0 degrees celsius
Coaxial Connector Series Designation:
Sma
Power Rating:
250.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 500.000 megahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5985-01-113-4182

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0