NSN 5985-01-114-5365

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-	114-5365
Application Design:	
Transmission line	
Body Material:	
Aluminum	
Body Style:	
Rectangular terminal/terminals on three surfaces	
Body Surface Treatment:	
Any acceptable	
Overall Length:	
0.147 inches	
Overall Height:	
0.122 inches	
Overall Width:	
0.035 inches	
Operating Tempurature Range:	
-55.0/+150.0 degrees celsius	
Voltage Standing Wave Ratio:	
1.30	
Input Impedance Rating In Ohms:	
50.0	
Output Impedance Rating In Ohms:	
50.0	
Power Rating:	
500.0 milliwatts average	
Rf Signal Attenuation In Decibels:	
7.0	
Voltage Standing Wave Ratio Frequency Range:	
+0.0/+18.0 gigahertz	
Attenuation Accuracy Reference Frequency:	
18.0 gigahertz	
Attenuation Accuracy In Decibels:	
-0.50/+0.50	
Mounting Method:	
Terminal	
Terminal Type And Quantity:	
3 surface contact	

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Terminal palladium and terminal gold

Precious Material:

Palladium and gold

NSN 5985-01-114-5365

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000