NSN 5985-01-114-7129

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-114-7129

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Err-090
Overall Length:
1.562 inches
Overall Diameter:
0.500 inches
Voltage Standing Wave Ratio:
1.25 and 1.35
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Attenuation Accuracy In Decibels:
-0.30/+0.30
Frequency Sensitivity Attenuation In Decibels:
Frequency Sensitivity Attenuation In Decibels: 0.001
0.001
0.001 Temperature Sensitivity Attenuation In Decibels:
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method:
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity:
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range:
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data:
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equip.
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equip. Shelf Life:
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equip. Shelf Life: N/a
0.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equip. Shelf Life: N/a
O.001 Temperature Sensitivity Attenuation In Decibels: O.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equip. Shelf Life: N/a Unit Of Measure:
O.001 Temperature Sensitivity Attenuation In Decibels: 0.0001 Mounting Method: Connector Terminal Type And Quantity: 1 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equip. Shelf Life: N/a Unit Of Measure: Demilitarization: