NSN 5985-01-116-5268

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-116-5268

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 all bends e-plane

End Application:

5840-01-046-7622, radar group, an/mst-t1

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.872 inches second flange

Flange Inside Height:

0.872 inches second flange

Flange Outside Width:

3.500 inches second flange

Flange Outside Height:

2.500 inches second flange

Flange Outside Diameter:

3.625 inches first flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.257 inches second flange single connection facility

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

NSN 5985-01-116-5268 Waveguide Assembly - Page 2 of 2



Flange Style:
Contact type second flange
Waveguide Length:
7.250 inches
Waveguide Center To Center Distance:
21.500 inches
Special Features:
H-plane offset bend, 1 flange 90 degree bend extending 3.72 in.
Flexibility:
Rigid all tubing segment
Material:
Aluminum alloy 6061 all tubing segment and flange
Style Designator:
Offset bend type
Thread Series Designator:
Unf first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0