NSN 5985-01-118-6857

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-118-6857

| Application Design: |
|--|
| Waveguide |
| Body Material: |
| Beryllium copper, qq-c-530 |
| Body Style: |
| 1b round, terminal/terminals in opposite surface |
| Body Surface Treatment: |
| Passivated, qq-p-35 |
| Overall Length: |
| 1.375 inches |
| Overall Height: |
| Between 0.302 inches and 0.322 inches |
| Overall Width: |
| Between 0.302 inches and 0.322 inches |
| Overall Diameter: |
| 0.360 inches |
| Operating Tempurature Range: |
| -54.0/+100.0 degrees celsius |
| End Application: |
| An/alr-62 |
| Coaxial Connector Series Designation: |
| Tps |
| Power Rating: |
| 10.0 milliwatts average |
| Rf Signal Attenuation In Decibels: |
| 14.0 |
| Attenuation Accuracy In Decibels: |
| -0.30/+0.30 |
| Connection Type Per Function: |
| Female input and male output |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 7.000 gigahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |
| Yes - demil/mli |

Fiig:

A20000