

View Online at <https://aerobasegroup.com/nsn/5985-01-119-6233>

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

Err-090

Body Surface Treatment:

Passivated

Overall Length:

1.040 inches

Overall Diameter:

0.312 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.35

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Wpm

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

30.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.4/+18.0 gigahertz

Attenuation Accuracy Reference Frequency:

18.0 gigahertz

Attenuation Accuracy In Decibels:

-1.00/+1.00

Connection Type Per Function:

Female input and male output

Unpackaged Unit Weight:

0.170 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000