## NSN 5985-01-120-0419

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-120-0419

Application Design:
Application Design: Transmission line
Body Material:
Aluminum alloy
·
Body Style:
Err-090
Body Surface Treatment:
Anodized
Overall Length:
3.520 inches
Overall Diameter:
1.550 inches
Voltage Standing Wave Ratio:
1.10
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
N Power Rating:
••
Power Rating:
Power Rating: 25.0 watts average and 5.0 kilowatts peak
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels:
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity:
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range:
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz Shelf Life:
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz Shelf Life: N/a
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz Shelf Life: N/a
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz Shelf Life: N/a Unit Of Measure:
Power Rating:  25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels:  30.0  Terminal Type And Quantity:  2 connector  Frequency Range:  Between 0.000 hertz and 1.500 gigahertz  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli
Power Rating: 25.0 watts average and 5.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1.500 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: