NSN 5985-01-120-9220

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-120-9220

Cross Sectional Shape: Internal, rectangular external, rectangular **Thread Class:** 2b single flange all connection facilities Thread Direction: Right-hand single flange all connection facilities Bend Angle In Deg: 90.0 single bend h-plane **Tubing Wall Construction Style:** Seamless single tubing segment Flange Quantity: Flange Inside Width: 1.255 inches first flange Flange Inside Height: 0.630 inches first flange Flange Outside Width: 1.875 inches second flange Flange Outside Height: 1.875 inches second flange Flange Inside Diameter: 1.625 inches single flange Flange Depth: 0.625 inches second flange Flange Connecting Hole Diameter: 0.169 inches single flange all connection facilities **Voltage Standing Wave Ratio:** 1.08 **Insertion Loss In Decibels:** 0.06 Thready Qty Per Inch (tpi): 32 single flange all connection facilities Maximum Operating Pressure: 30.0 pounds per square inch gage Waveguide Outside Width: 1.625 inches **Thread Size:** 0.164 inches single flange all connection facilities Waveguide Inside Width: 0.505 inches Waveguide Inside Height: 1.005 inches

2

NSN 5985-01-120-9220 Waveguide Assembly - Page 2 of 2



Waveguide	Outside Height:
1.625 inches	
Waveguide I	Longer Offset Distance:
1.869 inches	
Flange Conr	necting Facility And Quantity:
4 unthreaded	hole first flange all connection facilities
Flange Style	::
Cover type fi	rst flange
Waveguide	Offset Distance:
1.869 inches	
Flexibility:	
Rigid single t	ubing segment
Material:	
Metal single	tubing segment and flange
Style Desigr	nator:
Corner type	
Thread Serie	es Designator:
Unc single fla	ange all connection facilities
Specificatio	n Data:
81349-mil-w-	3970/16 government specification
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	tion:
No	
Fiig:	
A073a0	