## NSN 5985-01-120-9264

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-120-9264 **Application Design:** Transmission line **Body Material:** Any acceptable **Body Style:** Rectangular terminal/terminals on three surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 0.870 inches **Overall Height:** 0.055 inches **Overall Width:** 0.500 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 1.0 watts average **Rf Signal Attenuation In Decibels:** 2.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+8.0 gigahertz **Attenuation Accuracy Reference Frequency:** 1.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Mounting Method:** Printed circuit **Terminal Type And Quantity:** 3 ribbon Frequency Range: Between 0.000 hertz and 8.000 gigahertz **Precious Material And Location:** Lead gold **Precious Material:** 

Gold

## NSN 5985-01-120-9264

Fixed Attenuator - Page 2 of 2



| Fsc Application Data | Fsc | Ap | plic | ation | Data |
|----------------------|-----|----|------|-------|------|
|----------------------|-----|----|------|-------|------|

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000