NSN 5985-01-120-9264

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-120-9264

Application Design: Transmission line **Body Material:** Any acceptable **Body Style:** Rectangular terminal/terminals on three surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 0.870 inches **Overall Height:** 0.055 inches **Overall Width:** 0.500 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:**

50.0

Power Rating:

1.0 watts average

Rf Signal Attenuation In Decibels:

2.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+8.0 gigahertz

Attenuation Accuracy Reference Frequency:

1.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Mounting Method:

Printed circuit

Terminal Type And Quantity:

3 ribbon

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Precious Material And Location:

Lead gold

Precious Material:

Gold

NSN 5985-01-120-9264

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000