

View Online at <https://aerobasegroup.com/nsn/5985-01-120-9265>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

1b round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Passivated

**Overall Length:**

1.200 inches

**Overall Diameter:**

0.360 inches

**Voltage Standing Wave Ratio:**

1.15 and 1.20 and 1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Wpm

**Power Rating:**

2.0 watts average and 500.0 watts peak

**Rf Signal Attenuation In Decibels:**

5.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

**Attenuation Accuracy Reference Frequency:**

12.4 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Connection Type Per Function:**

Female input and male output

**Unpackaged Unit Weight:**

0.350 ounces

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 12.400 gigahertz

**Fsc Application Data:**

Antennas, waveguides and related equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000