NSN 5985-01-122-0564

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:



View Online at https://aerobasegroup.com/nsn/5985-01-122-0564

1b round, terminal/terminals in opposite surface								
Body Surface Treatment:								
Any acceptable								
Overall Length:								
1.020 inches								
Overall Diameter:								
0.280 inches								
Operating Tempurature Range:								
-65.0/+125.0 degrees celsius								
Voltage Standing Wave Ratio:								
1.07								
Input Impedance Rating In Ohms:								
50.0								
Output Impedance Rating In Ohms:								
50.0								
Coaxial Connector Series Designation:								
Sma								
Power Rating:								
2.0 watts average								
Rf Signal Attenuation In Decibels:								
Rf Signal Attenuation In Decibels: 16.0								
_								
16.0								
16.0 Voltage Standing Wave Ratio Frequency Range:								
16.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz								
16.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency:								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels:								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method:								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity:								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Fsc Application Data:								
Voltage Standing Wave Ratio Frequency Range: +0.0/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment								

NSN 5985-01-122-0564

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000