NSN 5985-01-122-4320

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-122-4320

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.840 inches
Overall Height:
0.500 inches
Overall Width:
1.720 inches
Unthreaded Mounting Hole Diameter:
0.094 inches
Operating Tempurature Range:
-54.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+35.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 5.400 gigahertz and 6.000 gigahertz
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Terminal Type And Quantity:
1 connector, coaxial, male and 1 connector, coaxial, female
Shelf Life:

N/a

NSN 5985-01-122-4320

Variable Attenuator - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A223a0