NSN 5985-01-124-0072

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-124-0072

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.870 inches
Overall Height:
0.900 inches
Overall Width:
1.500 inches
Scale Linearity:
Linear
Scale Division Quantity:
70
Distance Between Mounting Facility Centers:
3.000 inches
Operating Tempurature Range:
-20.0/+75.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 100.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.4
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

NSN 5985-01-124-0072

Variable Attenuator - Page 2 of 2



Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.112 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A223a0