NSN 5985-01-124-9694

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-124-9694

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.352 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.352 inches
Overall Height:
1.875 inches
Overall Width:
1.875 inches
Scale Linearity:
Linear
Scale Division Quantity:
6
Unthreaded Mounting Hole Diameter:
0.169 inches
Operating Tempurature Range:
-65.0/+155.0 degrees fahrenheit
Voltage Standing Wave Ratio:
1.10
Power Rating:
50.0 watts average
Waveguide Flange Type:
Cover
Waveguide Flange Designation:
Ug-138/u
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+6.0
Attenuation Variation Method:
Continuous
Vernier Scale Division Quantity:
1
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:

Between 900.000 megahertz and 8.400 gigahertz

NSN 5985-01-124-9694

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Terminal Type And Quantity:
2 flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0