NSN 5985-01-125-0889

Variable Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-125-0889

Transmission line
Body Style:
Irregular
Overall Length:
4.628 inches
Overall Height:
1.000 inches
Overall Width:
2.220 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.125 inches
Distance Between Mounting Facility Centers:
1.875 inches
Coaxial Connector Series Designation:
Tnc
Mounting Facility Screw Thread Series Designator:
Unf
Overall Attenuation Range In Decibels:
+0.0/+6.0
Attenuation Variation Method:
Attenuation Variation Method: Stepped
_
Stepped
Step Position Quantity:
Stepped Step Position Quantity: 3
Stepped Step Position Quantity: 3 Attenuation Per Step In Decibels:
Stepped Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0
Stepped Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity:
Stepped Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range:
Stepped Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz
Stepped Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity:
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity: 32 per inch
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern:
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Two position in-line
Step Position Quantity: 3 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 terminal and 2 threaded bushing Frequency Range: Between 0.000 hertz and 20.000 megahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Two position in-line Shaft Type:

NSN 5985-01-125-0889

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0