

View Online at <https://aerobasegroup.com/nsn/5985-01-126-8288>

Application Design:

Transmission line

Body Material:

Aluminum

Body Style:

Coaxial type

Overall Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.590 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.840 inches

Overall Height:

0.500 inches

Overall Width:

1.760 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

5.0 watts average and 3.0 kilowatts peak

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Accuracy Reference Frequency:

18.0 gigahertz

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 12.000 gigahertz and 18.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.00

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.112 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A223a0