NSN 5985-01-132-8750

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-132-8750
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
Between 0.840 inches and 0.880 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
5.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+8.0 gigahertz
Attenuation Accuracy Reference Frequency:
8.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output
Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-132-8750

Fixed Attenuator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000