NSN 5985-01-134-1177

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-134-1177

view Online at https://aerobasegroup.com/nsn/5965-01-134-1177
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Terminal Material:
Steel, stainless
Overall Length:
Between 2.180 inches and 2.300 inches
Overall Diameter:
0.840 inches
End Application:
Radar set, an/spg-51d
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Ν
Power Rating:
5.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
8.0
Voltage Standing Wave Ratio Frequency Range:
+5.4/+5.9 gigahertz
Attenuation Accuracy In Decibels:
-0.22/+0.22
Frequency Sensitivity Attenuation In Decibels:
0.44
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
3.000 pounds
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 5.400 gigahertz and 5.900 gigahertz

NSN 5985-01-134-1177

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000