NSN 5985-01-134-4952

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-134-4952

·
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
2.100 inches
Overall Width:
3.000 inches
Operating Tempurature Range:
-40.0/+62.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+50.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 2.900 gigahertz and 3.100 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.50/+1.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob

Four position rectangular

Mounting Facility Pattern:

NSN 5985-01-134-4952

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.138 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0