# NSN 5985-01-134-5034

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-134-5034

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**End Application:** 

Radar set an/aps-94

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

#### Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

#### Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

# Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

# Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

#### Flange Depth:

0.423 inches second flange and 0.453 inches second flange

# Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

# **Voltage Standing Wave Ratio:**

1.06

#### Thready Qty Per Inch (tpi):

32 first flange all connection facilities

# Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

# Thread Size:

0.164 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

# Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

# **Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

# **NSN 5985-01-134-5034** Waveguide Assembly - Page 2 of 2



Waveguide First Leg Length:
0.930 inches
Waveguide Fifth Leg Length:
4.610 inches
Flange Style:
Cover type second flange
Waveguide Second Leg Length:
3.500 inches
Waveguide Sixth Leg Length:
2.600 inches
Waveguide Third Leg Length:
4.540 inches
Waveguide Fourth Leg Length:
0.900 inches
Flexibility:
Flexible single tubing segment
Material:
Rubber chloroprene single tubing jacket
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver single tubing segment inside surfaces
Style Designator:
Five bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0