NSN 5985-01-134-5036

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-134-5036

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Bend Angle In Deg:

75.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches first flange and 1.006 inches first flange

Flange Inside Height:

0.503 inches first flange and 0.506 inches first flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches first flange all connection facilities and 0.172 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.06

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

Between 4.625 inches and 4.655 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

NSN 5985-01-134-5036 Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type first flange
Waveguide Offset Distance:
2.560 inches
Special Features:
Frequency range 9.0-9.5 ghz; cw power is 30w at27 psig
Flexibility:
Flexible single tubing segment
Material:
Copper alloy single tubing segment
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver single tubing segment and flange inside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc second flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0