NSN 5985-01-134-5049

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-134-5049

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Rectangular terminal/terminals on three surfaces
Body Surface Treatment:
Gold plated
Overall Length:
0.647 inches
Overall Height:
0.035 inches
Overall Width:
0.397 inches
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
4.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Unpackaged Unit Weight:
0.003 pounds
Mounting Method:
Terminal
Terminal Type And Quantity:
3 ribbon
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold

NSN 5985-01-134-5049

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000