NSN 5985-01-134-5049

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-134-5049

Application Design:					
Transmission line					
Body Material:					
Any acceptable					
Body Style:					
Rectangular terminal/terminals on three surfaces					
Body Surface Treatment:					
Gold plated					
Overall Length:					
0.647 inches					
Overall Height:					
0.035 inches					
Overall Width:					
0.397 inches					
Voltage Standing Wave Ratio:					
1.30					
Input Impedance Rating In Ohms:					
50.0					
Output Impedance Rating In Ohms:					
50.0					
Power Rating:					
1.0 watts average					
Rf Signal Attenuation In Decibels:					
4.0					
Voltage Standing Wave Ratio Frequency Range:					
+0.0/+18.0 gigahertz					
Attenuation Accuracy Reference Frequency:					
18.0 gigahertz					
Attenuation Accuracy In Decibels:					
-0.50/+0.50					
Unpackaged Unit Weight:					
0.003 pounds					
Mounting Method:					
Terminal					
Terminal Type And Quantity:					
3 ribbon					
Frequency Range:					
Between 0.000 hertz and 18.000 gigahertz					
Precious Material And Location:					
Contact surfaces gold					
Precious Material:					
Gold					

NSN 5985-01-134-5049

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000