NSN 5985-01-136-2372

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-136-2372

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Err-090
Body Surface Treatment:
Anodized
Overall Length:
2.750 inches
Overall Diameter:
1.610 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
Power Rating: 10.0 watts average
•
10.0 watts average
10.0 watts average Rf Signal Attenuation In Decibels:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a Unit Of Measure:
10.0 watts average Rf Signal Attenuation In Decibels: 10.0 Attenuation Accuracy In Decibels: -0.50/+0.50 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: