## NSN 5985-01-136-2373

Fixed Attenuator - Page 1 of 2

Between 0.000 hertz and 18.000 gigahertz



View Online at https://aerobasegroup.com/nsn/5985-01-136-2373

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Err-090
Body Surface Treatment:
Anodized
Overall Length:
2.750 inches
Overall Diameter:
1.610 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
4.000 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:

## NSN 5985-01-136-2373

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000