## NSN 5985-01-136-7946

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-136-7946

Analisation Design
Application Design:
Body Material:
Steel, corrosion resisting
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Any acceptable
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
1.000 inches
Overall Diameter:
0.375 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.07
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz

## NSN 5985-01-136-7946

Fixed Attenuator - Page 2 of 2



## **Fsc Application Data:**

Antennas, waveguides and related equip.

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A20000