NSN 5985-01-137-6527

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-137-6527

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.760 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.800 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.050 inches
Overall Height:
2.310 inches
Overall Width:
0.880 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Voltage Standing Wave Ratio:
1.70
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.5
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 0.500 gigahertz and 4.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-2.00/+2.00
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 hinding post and 2 connector, coaxial, female and 1 connector, recentacle

NSN 5985-01-137-6527

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0