## NSN 5985-01-137-6528

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-137-6528

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.760 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.800 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.050 inches
Overall Height:
2.310 inches
Overall Width:
0.880 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Voltage Standing Wave Ratio:
1.80
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
3.0
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 2.000 gigahertz and 8.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-2.00/+2.00
Adjustment Device Type And Quantity:
1 electronic, programmable
Impedance Rating In Ohms:
3000.0 input
Special Features:
Operates at 15 volts
Terminal Type And Quantity:

2 binding post and 2 connector, coaxial, female and 1 connector, receptacle

## NSN 5985-01-137-6528

Variable Attenuator - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0