## NSN 5985-01-138-6143

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-138-6143

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
4.520 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 3.495 inches and 3.505 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 3.495 inches and 3.505 inches
Overall Height:
2.720 inches
Overall Width:
4.520 inches
Scale Linearity:
Linear
Scale Division Quantity:
100
Unthreaded Mounting Hole Diameter:
Between 0.149 inches and 0.159 inches
Operating Tempurature Range:
-28.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.50 and 1.80
Coaxial Connector Series Designation:
N
Power Rating:
15.0 watts average
Overall Attenuation Range In Decibels:
+6.0/+106.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 960.000 megahertz and 1.215 gigahertz
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:

50.0 input-output

## NSN 5985-01-138-6143

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	<b>/</b> :
-----------------	--------------	------------

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0