## NSN 5985-01-139-2735

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-139-2735

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.250 inches
Overall Height:
2.500 inches
Overall Width:
1.500 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Insertion Loss At Minimum Attenuation In Maximum Decibels:
3.0
Overall Attenuation Range In Decibels:
+0.0/+3.0
Step Position Quantity:
otop i conton quantity.
7
7
7 Frequency Range:
7 Frequency Range: Between 0.000 megahertz and 500.000 megahertz
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels:
7 Frequency Range: Between 0.000 megahertz and 500.000 megahertz Overall Attenuation Accuracy In Decibels: -0.10/+0.10
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels:
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity:
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features:
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features: Sma-to-sma semirigid coaxial jumper on two connectors
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features: Sma-to-sma semirigid coaxial jumper on two connectors  Shelf Life:
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features: Sma-to-sma semirigid coaxial jumper on two connectors  Shelf Life: N/a
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features: Sma-to-sma semirigid coaxial jumper on two connectors  Shelf Life: N/a
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features: Sma-to-sma semirigid coaxial jumper on two connectors  Shelf Life: N/a  Unit Of Measure:
Frequency Range: Between 0.000 megahertz and 500.000 megahertz  Overall Attenuation Accuracy In Decibels: -0.10/+0.10  Segment Attenuation Range In Decibels: +0.00/+111.00  Adjustment Device Type And Quantity: 1 knob  Special Features: Sma-to-sma semirigid coaxial jumper on two connectors  Shelf Life: N/a  Unit Of Measure:  Demilitarization: