# NSN 5985-01-141-5652

Fixed Attenuator - Page 1 of 2





# **Application Design:**

Transmission line

#### **Body Material:**

Metal

# Body Style:

1b round, terminal/terminals in opposite surface

# **Body Surface Treatment:**

Any acceptable

#### **Overall Length:**

2.190 inches

#### **Overall Diameter:**

0.590 inches

#### **Operating Tempurature Range:**

-55.0/+100.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.20 and 1.35

### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Bnc

#### **Power Rating:**

1.0 kilowatts peak

#### **Rf Signal Attenuation In Decibels:**

6.0

#### Voltage Standing Wave Ratio Frequency Range:

+0.0/+1.5 gigahertz

# Attenuation Accuracy In Decibels:

-0.50/+0.50

#### Mounting Method:

Connector

#### **Terminal Type And Quantity:**

2 connector

#### **Frequency Range:**

Between 0.000 hertz and 1.500 gigahertz

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# **NSN 5985-01-141-5652** Fixed Attenuator - Page 2 of 2

Fiig: A20000

